

Puget Sound Naval Shipyard & Intermediate
Maintenance Facility Project ENVVEST
Community Advisory Committee Meeting
Oct. 26, 2004
Jackson Park Community Center
Bremerton, WA

Update on Fecal Coliform Technical Study

Presented by:


Dr. Robert K. Johnston
Marine Environmental Support Office – NW
Space and Naval Warfare Systems Center
Bremerton, WA

Update on Fecal Coliform Technical Study

- Introduction
- Highlights of Technical Study
 - Historical Data
 - Storm Event Monitoring
 - Landscape Analysis
 - Loading Analysis
- Next Steps
 - Modeling and Scenario Analysis
 - Develop Water Cleanup Plan

Beneficial Uses

- ***Shellfish Harvest***
- ***Fishing***
- ***Contact Recreation***
 - *Swimming*
 - *Boating*
- ***Aquatic Life (Fish & Wildlife Habitat)***
- ***Shoreline Development***
- ***Commercial & Industrial Activity***
 - *Shipping*
 - *Marinas*
 - *Shipyards*





Water Quality Criteria

- Standards developed to protect beneficial uses (Shellfishing)
- PART 1: Average Concentration
 - 14 colony forming units per 100 ml
 - 14 cfu/100 ml (Marine)
 - 100 cfu/100 ml (Stream)
- PART 2: Spikes
 - No more than 10% of the samples can exceed
 - 43 cfu/100 ml (Marine)
 - 200 cfu/100 ml (Streams)



Data Analysis

- Historical Data
 - Kitsap County Health District (KCHD)
 - WA Department of Health (DOH)
 - Kitsap County Surface and Stormwater Management (SSWM)
- ENVVEST Storm Event Monitoring
 - Measure runoff during storm events
- Landscape Analysis
 - Relate water quality from runoff to landuse






Nearshore & Marine






Stream Data




Stream Data










Simulating FC Loading

- Flow Data
 - Volume of water discharged (cubic feet per second – cfs)
 - Only limited number of streams and storm water outfalls are gauged
 - Watershed model predicts flows for all “pour points”
- Concentration Data
 - FC cfu/100 ml being discharged
 - No data for many streams and outfalls
 - Estimate concentration from existing data
- Load = Flow x Concentration
 - FC cfu/day (millions of counts)


Predicting FC Loading




Next Steps

- Verify Integrated Model
- Conduct Scenario Analysis
- Develop Water Cleanup Plan

Model Verification



Simulating Loads



Technical Reports

- An Analysis of Microbial Pollution in the Sinclair-Dyes Inlet Watershed
- Watershed Model Calibration Report for Streams and Storm Water
- Integrated Model Verification Report
- Simulation and Scenario Analysis Report